


150 Watt LED Flood Light


EO-FLW-150W



SPECIFICATIONS	
Model Number	EO-FLW-150W
Driver	Built In
Power Consumption	161 (LCP)
LED	Citizen
	CLL042-1218A5-503M1A2
LED Luminous Flux	13,923 Lumens
LED Luminous Efficiency	86.48 lm/watt
Average Illumination	4m - 300 lux
	6m – 140 lux
	8m – 80 lux
	7m – 50 lux
Illuminated Area	At 4m – 11m diameter
	At 6m –17m diameter
	At 8m – 22m diameter
	At 10m –28m diameter
	At 12m –33m diameter
Light Angle	120 [°]
Input Voltage	240 Volts, 50 Hz
Power Factor	> 0.96
Storage Temperature	-25°C - +65°C
Working Environment	-25°C - +50C°
Body Material	Die Cast Aluminium Alloy and Glass
IP Rating	IP 65
Rendering Index CRI	Ra 69.0
Colour Temperature	6000 Kelvin Standard
	Other kelvins available to order
Certificate	CS 9567N
	IEC 60598.2.5 IEC 61346.2.13:2006
	V N28689
Life Expectancy	>50,000 + hrs
Net Weight	14 kg
Warranty	5 years







This product is eligible for the NSW Energy Saving Scheme For more information visit our website: <u>www.eolighting.com.au</u>

B

© Summit LED Energy Australia Pty Ltd t/as eo lighting

Head Office Sydney: Unit 5G, 256 New Line Road, Dural, NSW, 2158

Ph: 02 9653 9909 Fax: 02 9653 9959 www.eolighting.com.au

Melbourne Canber

Green Energy LED Solutions