
150 Watt LED Linear High Bay Light




SPECIFICATIONS	
Model Number	EO-LHB-150W
Driver	Built - in
Power Consumption	154.1w (LCP)
LED	Nichia NF2W757GRT-V1
LED Initial Flux	21,012 lumens
Average/ Max Lumens	Avg Max
	5m – 637 lux 839 lux
	6m - 442 lux 583 lux
	8m – 249 lux 323 lux
	10m – 159 lux 210 lux
	12m – 111 lux 146 lux
ED Luminous Efficiency	> 140 lumens / watt
Beam Angle	40 x 80°
Power Factor	>0.95
Working Voltage	AC 220-265 voltage
Input Voltage	240 Volts, 50 Hz
Lamps Efficiency	>90%
Material	Aluminium House – PC Lens
Working Temperature	- 40°C to + 40°C
Luminaire Base temperature	65'C (at room temp 30')
IP Rating	IP 65
Colour Temperature	Cool White 4700 kelvin
	Daylight 5300 kelvin
Colour Index	>Ra70
Certificate	SAA160246
	60598.2.1:2014, 60598.1:2013
	V N28689
Dimensions	L986 x W190 x H118mm
Net Weight	6.2.Kg
Life Expectancy	50,000 + Hrs
Warranty	7 Years




EO-LHB-150W






Thermal Management



Each beam of light is utilized to illuminate the right place and lumen waste is less than 5% compared with common LED high bays.



IES Files available

© Summit LED Energy Australia Pty Ltd t/as eo lighting Head Office Sydney: Unit 5G, 256 New Line Road, Dural, NSW, 2158 Ph: 02 9653 9909 Fax: 02 9653 9959 www.eolighting.com.au Aelbourne Canberra Brisbane ydney Adelaide Perth Green Energy LED Solutions